



Dimensions in mm.

SIZE		0.4	0.8	1.6		3.2		6		8		15		24	
Static Torque	kgm	0.4	0.8	1.6		3.2		6		8		15		24	
Exciting Voltage	DC-V	24,96,190	24,96,190	24,96,190		24,96,190		24,96,190		24,96,190		24,96,190		24,96,190	
Capacity (at 20°C)	W	20	25	30		40		50		65		85		110	
Max. Revolution	RPM	3000	3000	3000		3000		3000		3000		2000		2000	
Bore Standard	Dia d_{H7}	11	15	15	20	20	25	25	30	25	30	35	40	40	50
	Keyway b x l	4 x 1.5	5 x 2	5 x 2	5 x 2	5 x 2	7 x 3	7 x 3	7 x 3	7 x 3	7 x 3	10 x 3.5	10 x 3.5	10 x 3.5	12 x 3.5
Diameter	A	84	102	127		147		162		188		215		252	
	B	72	90	112		132		145		170		196		230	
	C	30	45	56		62		74		84		100		120	
	D_{H7}	20	30	40		45		55		65		75		90	
	E	19	24	35		40		48		52		62		72	
	F	95	110	140		165		185		220		260		300	
	G	3 x 4.5	3 x 5.5	3 x 6.5		3 x 6.5		3 x 9		3 x 9		6 x 9		6 x 11	
	H	3 x 4.5	3 x 5.5	3 x 6.5		3 x 6.5		3 x 9		3 x 9		3 x 9		3 x 11	
Length	L	44	48	59		66		76		84		96		108	
	M	18	20	20		25		30		30		35		40	
	N	7.8	9.5	12.5		12		14		14		15		17.5	
	P	17	18	25		31		36		40		33		47	
	S	6	7	9		9		11		11		11		11	
	T	3.5	4	4		5		5		6		6		8	
	V	10°	8°	8°		8°		8°		8°		12°		12°	
Air Gap	a	0.2	0.2	0.2		0.3		0.3		0.3		0.4		0.4	
Weight	kg	1.2	1.8	3.0		4.8		7.3		12		18		27	